

Threaded Zinc Insert
Precast Concrete Insert
Zinc Alloy Threaded Insert

Part No.	Bolt Size	Height	SWL
HMY-P15T	1/4"-20NC	1-1/2"	750lbs.
HMY-P24T	3/8"-16NC	1"	1,125lbs.
HMY-P25T	3/8"-16NC	1-3/8"	1,300lbs.
HMY-P35T	1/2"-13NC	1-1/2"	1,500lbs.
HMY-P36T	1/2"-13NC	2-7/8"	3,600lbs.
HMY-P45T	5/8"-11NC	1-11/16"	1,900lbs.
HMY-P46T	5/8"-11NC	2-7/8"	4,625lbs.
HMY-P55T	3/4"-10NC	1-11/16"	2,275lbs.
HMY-P56T	3/4"-10NC	2-7/8"	4,550lbs.
HMY-P25TOB	3/8"-16NC	1-3/8"	1,300lbs.
HMY-P35TOB	1/2"-13NC	1-1/2"	1,500lbs.
HMY-HLZ	1/2"-13 NC	2-3/8"	550lbs.

Safety Factor: approximately 3:1 in 3,500 psi normal weight concrete.

All safe working loads should be used only as a guide.

Precast Concrete Inserts are not intended to be used for lifting.

Material: Zinc Alloy

