


www.lyhigh.com

Wall Brace Insert





WORKING LOADS IN LBS. IN 2500 PSI CONCRETE, 2.0:1 SAFETY FACTOR

CONUMETE, 2.0.1 SAFETT FACTOR			
ltem Number	Conc. Thick. in inches	_Face Tension	Face Shear
B75050	5"	7,800	8,200
B75055	5-1/2"	9,625	10,150
B75060	6"	10,150	10,150
B75062	6-1/4"	10,150	10,150
B75065	6-1/2"	10,150	10,150
B75070	7"	10,150	10,150
B75072	7-1/4"	10,150	10,150
B75075	7-1/2"	10,150	10,150
B75080	8"	10,150	10,150
B75082	8-1/4"	10,150	10,150
B75085	8-1/2"	10,150	10,150
B75090	9"	10,150	10,150
B75092	9-1/4"	10,150	10,150
B75095	9-1/2"	10,150	10,150
B75100	10"	10,150	10,150
B75105	10-1/2"	10,150	10,150
B75110	11"	10,150	10,150
B75112	11-1/4"	10,150	10,150
B75115	11-1/2"	10,150	10,150
B75120	12"	10,150	10,150

3/4" diameter coil insert height is 1/2" less than panel thickness. Available in 1/2" increments from 5" through 12".

